

ATX 2.3 EPS 2.92

Extreme Models Frequency Conversion 800W

Specifications

- > Support EPS 2.92
- > 4 12V Rails
- > SATA Connectors
- > Efficiency: >82% Typical
- > Silent 135mm Intake Fan
- > Thermal Control Technology
- > Protection Circuitry
- > Safety Approval: CB, UL, TUV, FCC, CE
- > Dimensions: 150*165*86 mm
- > APFC (Active Power Factor Correction)

Included in Box

- > 1 x 800 Watt Power Supply Unit
- > 1 x Power Cable
- > 4 x Mounting Screws

Connectors

- > 1 x 24-Pin (20+4-Pin) Motherboard Connector
- > 1 x 8-Pin CPU 12V Power Connector
- > 1 x 4-Pin CPU 12V Power Connector
- > 6 x 4-Pin Molex Connectors
- > 2 x 4-Pin Floppy Connectors
- > 6 x SATA Connectors
- > 2 x PCIE 6+2-PinPower Connectors
- > 2 x PCIE 6-PinPower Connectors

Works with the following motherboards

- > PCI Express
- > AGP
- > PCI

Part Number: **AD-M0800A2-71**

Works with **AGP, PCI, PCI Express®**

Includes four **PCI Express** Connectors for **Dual Graphics Card Support**, Features new **8-Pin PCI Express Connect**
4 12V Rails
APFC (Active Power Factor Correction)



Fully Sleeved Cables 500mm

ANDYSON International Co., Ltd.
3F., No.153, Sec.3, Beishen Rd., Shenkeng, Taipei County 222, Taiwan
TEL +886 2 26626259 FAX +886 2 26640738
Email: b2b@andysonet.com
Website: www.andysonpower.com



ANDYSON AD-M0800A2-71

800WATT POWER SUPPLY • ATX12V 2.2 / EPS 12V 2.91

| | | | | | | | | |
|----------------------|---------------------------|-----|-----------------|-------|-------|-------|------|-------|
| AC INPUT | 100-240VAC, 9-5A, 50-60Hz | | | | | | | |
| DC OUTPUT | +3.3V | +5V | +12V1 | +12V2 | +12V3 | +12V4 | -12V | +5VSB |
| MAX OUTPUT CURRENT | 30A | 30A | 22A | 22A | 36A | 36A | 0.5A | 3A |
| MAX COMBINED WATTAGE | 170W | | 780W, Total 65A | | | | 20W | |
| | 800W | | | | | | | |



CAUTION: HAZARDOUS AREA
DO NOT REMOVE THIS COVER
SELECT THE RIGHT VOLTAGE



| | 800W | 900W | 1000W | 1100W | 1200W |
|---------------|------|------|-------|-------|-------|
| ATX 20+4 PIN | x1 | x1 | x1 | x1 | x1 |
| ATX 8 PIN | x1 | x1 | x1 | x1 | x1 |
| ATX 4+4 PIN | | | | | x1 |
| ATX 4 PIN | x1 | x1 | x1 | x1 | x1 |
| PCI-E 6+2 PIN | x2 | x2 | x3 | x3 | x3 |
| PCI-E 6 PIN | x2 | x2 | x3 | x3 | x3 |
| SATA | x6 | x6 | x9 | x9 | x9 |
| Molex 4 PIN | x6 | x6 | x6 | x6 | x6 |
| FDD | x2 | x2 | x2 | x2 | x2 |

ANDYSON
The Art of Power

ATX 2.3 EPS 2.92

Extreme Models Frequency Conversion 900W

Specifications

- > Support EPS 2.92
- > 4 12V Rails
- > SATA Connectors
- > Efficiency: >82% Typical
- > Silent 135mm Intake Fan
- > Thermal Control Technology
- > Protection Circuitry
- > Safety Approval: CB, UL, TUV, FCC, CE
- > Dimensions: 150*165*86 mm
- > APFC (Active Power Factor Correction)

Included in Box

- > 1 x 900 Watt Power Supply Unit
- > 1 x Power Cable
- > 4 x Mounting Screws

Connectors

- > 1 x 24-Pin (20+4-Pin) Motherboard Connector
- > 1 x 8-Pin CPU 12V Power Connector
- > 1 x 4-Pin CPU 12V Power Connector
- > 6 x 4-Pin Molex Connectors
- > 2 x 4-Pin Floppy Connectors
- > 6 x SATA Connectors
- > 2 x PCIE 6+2-PinPower Connectors
- > 2 x PCIE 6-PinPower Connectors

Works with the following motherboards

- > PCI Express
- > AGP
- > PCI

Part Number: **AD-M0900A2-71**

Works with **AGP, PCI, PCI Express®**

Includes four **PCI Express** Connectors for **Dual Graphics Card** Support , Features new **8-Pin PCI Express** Connect
4 12V Rails

APFC (Active Power Factor Correction)



Fully Sleeved Cables 500mm



ANDYSON AD-M0900A2-71

900WATT POWER SUPPLY • ATX12V 2.2 / EPS 12V 2.91

| | | | | | | | | |
|----------------------|------------------------------|-----|-----------------|-------|-------|-------|------|-------|
| AC INPUT | 100-240VAC, 10-5.5A, 50-60Hz | | | | | | | |
| DC OUTPUT | +3.3V | +5V | +12V1 | +12V2 | +12V3 | +12V4 | -12V | +5VSB |
| MAX OUTPUT CURRENT | 30A | 30A | 28A | 28A | 36A | 36A | 0.5A | 3A |
| MAX COMBINED WATTAGE | 170W | | 888W, Total 74A | | | | 20W | |
| | 900W | | | | | | | |



CAUTION: HAZARDOUS AREA
DO NOT REMOVE THIS COVER
SELECT THE RIGHT VOLTAGE



FCC Class B Compliance
FOR HOME USE ONLY



UL Listed
E239028



| | | 800W | 900W | 1000W | 1100W | 1200W |
|--|---------------|------|------|-------|-------|-------|
| | ATX 20+4 PIN | x1 | x1 | x1 | x1 | x1 |
| | ATX 8 PIN | x1 | x1 | x1 | x1 | x1 |
| | ATX 4+4 PIN | | | | | x1 |
| | ATX 4 PIN | x1 | x1 | x1 | x1 | x1 |
| | PCI-E 6+2 PIN | x2 | x2 | x3 | x3 | x3 |
| | PCI-E 6 PIN | x2 | x2 | x3 | x3 | x3 |
| | SATA | x6 | x6 | x9 | x9 | x9 |
| | Molex 4 PIN | x6 | x6 | x6 | x6 | x6 |
| | FDD | x2 | x2 | x2 | x2 | x2 |

ANDYSON International Co., Ltd.
3F., No.153, Sec.3, Beishen Rd., Shenkeng, Taipei County 222, Taiwan
TEL +886 2 26626259 FAX +886 2 26640738
Email: b2b@andysonet.com
Website: www.andysonpower.com

ANDYSON
The Art of Power

ATX 2.3 EPS 2.92

Extreme Models Frequency Conversion 1000W

Specifications

- > Support EPS 2.92
- > 4 12V Rails
- > SATA Connectors
- > Efficiency: >82% Typical
- > Silent 135mm Intake Fan
- > Thermal Control Technology
- > Protection Circuitry
- > Safety Approval: CB, UL, TUV, FCC, CE
- > Dimensions: 150*165*86 mm
- > APFC (Active Power Factor Correction)

Included in Box

- > 1 x 1000 Watt Power Supply Unit
- > 1 x Power Cable
- > 4 x Mounting Screws

Connectors

- > 1 x 24-Pin (20+4-Pin) Motherboard Connector
- > 1 x 8-Pin CPU 12V Power Connector
- > 1 x 4-Pin CPU 12V Power Connector
- > 6 x 4-Pin Molex Connectors
- > 2 x 4-Pin Floppy Connectors
- > 9 x SATA Connectors
- > 3 x PCIe 6+2-PinPower Connectors
- > 3 x PCIe 6-PinPower Connectors

Works with the following motherboards

- > PCI Express
- > AGP
- > PCI

Part Number:**AD-M1000A2-71**

Works with **AGP, PCI, PCI Express®**

Includes four **PCI Express** Connectors for
Dual Graphics Card Support , Features new
8-Pin PCI Express Connect
4 12V Rails

APFC (Active Power Factor Correction)



Fully Sleeved Cables 500mm



ANDYSON AD-M1000A2-71

1000WATT POWER SUPPLY • ATX12V 2.2 / EPS 12V 2.91

| | | | | | | | |
|----------------------|------------------------------|-----|-----------------|-------|-------|-------|------------|
| AC INPUT | 100-240VAC, 10-5.5A, 50-60Hz | | | | | | |
| DC OUTPUT | +3.3V | +5V | +12V1 | +12V2 | +12V3 | +12V4 | -12V +5VSB |
| MAX OUTPUT CURRENT | 30A | 30A | 36A | 36A | 36A | 36A | 0.5A 3A |
| MAX COMBINED WATTAGE | 170W | | 984W, Total 82A | | | 20W | |
| | 1000W | | | | | | |



CAUTION: HAZARDOUS AREA
DO NOT REMOVE THIS COVER
SELECT THE RIGHT VOLTAGE



| | | 800W | 900W | 1000W | 1100W | 1200W |
|--|---------------|------|------|-------|-------|-------|
| | ATX 20+4 PIN | x1 | x1 | x1 | x1 | x1 |
| | ATX 8 PIN | x1 | x1 | x1 | x1 | x1 |
| | ATX 4+4 PIN | | | | | x1 |
| | ATX 4 PIN | x1 | x1 | x1 | x1 | x1 |
| | PCI-E 6+2 PIN | x2 | x2 | x3 | x3 | x3 |
| | PCI-E 6 PIN | x2 | x2 | x3 | x3 | x3 |
| | SATA | x6 | x6 | x9 | x9 | x9 |
| | Molex 4 PIN | x6 | x6 | x6 | x6 | x6 |
| | FDD | x2 | x2 | x2 | x2 | x2 |

ANDYSON International Co., Ltd.
3F., No.153, Sec.3, Beishen Rd., Shenkeng, Taipei County 222, Taiwan
TEL +886 2 26626259 FAX +886 2 26640738
Email: b2b@andysonet.com
Website: www.andysonpower.com

ANDYSON
The Art of Power